

Artix™ UltraScale+ FPGA

OVERVIEW

Artix UltraScale+ devices are the industry's only cost-optimized FPGAs based on a production-proven 16nm architecture for best-in-class performance/watt, along with packaging innovation for ultra-compact form factor and compute density.

With up to 16Gb/s transceivers for advanced protocols, and the highest DSP performance in their class, Artix UltraScale+ FPGAs match I/O bandwidth to compute to maximize system performance for cost-sensitive and low power applications in machine vision, secure networking, 4K broadcast, and a range of industrial IoT and edge markets.

HIGHLIGHTS

Highest I/O Bandwidth and Compute in a Cost-Optimized FPGA

- > 2.4X fabric performance/watt vs. Artix-7 FPGAs
- > Up to 16Gb/s transceivers for emerging protocols in networking, video, and vision
- > Exceptional fixed- and floating-point DSP compute in its class
- > 2500Mb/s MIPI performance for the latest sensor technologies

Packaging Innovation for Industry's Highest Compute Density


- > Integrated Fan-Out (InFO) packaging for ultra compact form factor (10.2x8.5mm)
- > "Near die-size" ball pitch (0.5mm) for no loss of pins
- > 75% less area (than flip-chip packaging) for better thermal & power distribution
- > Exceptional I/O bandwidth and compute / mm² in its class

Multi-Level Safeguards for Cybersecurity and IP Protection

- > RSA-2048 authentication to verify design source
- > AES-CGM decryption (NIST-approved) with faster configuration
- > Security monitor IP to adapt to security threats across the product life cycle
- > Range of safeguards - including anti-tamper and SEU performance

Scalable to Mid-Range and High-End UltraScale+ FPGA Families

- > Scale to higher logic density, compute, and transceiver performance as needed
- > Common silicon architecture, tool flows, and ecosystem for a common platform
- > Preserve investments in SW, IP, tools, and PCB design across the portfolio
- > Leverage a platform strategy for developing a multi-product portfolio



TARGET APPLICATIONS

Industrial

- > Machine Vision
- > Industrial Networking (Time-Sensitive Networking)
- > Industrial Controllers

Medical

- > Portable and Desktop Ultrasound
- > Surgical Vision
- > Endoscopy

Networking

- > Cost-sensitive Nx10G and 25G Networking
- > Network Bridging for Nx100G Systems

AV Broadcasting

- > LED Video Walls
- > Digital Signage
- > KVM Switch
- > Video Mini-Converters

Aerospace & Defense




- > MILCOM Radio
- > Missiles & Munitions

FEATURES

Artix UltraScale+ FPGAs leverage production-proven architectural blocks of the UltraScale™ architecture.

FEATURES OVERVIEW	
Enhanced Programmable Logic Architecture	<ul style="list-style-type: none"> > Based on TSMC's 16nm FinFET+ process > 2.4X performance/watt vs. Artix-7 FPGAs > Voltage scaling to tune power and performance on the same device > Enhanced CLB/LUTs, routing, and ASIC-class clocking for high utilization
High-Performance Transceivers	<ul style="list-style-type: none"> > Up to 16Gb/s transceiver line rates (minimum of 12Gb/s across the family) > Power-optimized architecture vs. Artix-7 FPGAs > Single oscillator for fabric and SerDes eliminates extra clocking components
PCI Express® Gen3, Gen4 Support	<ul style="list-style-type: none"> > PCI Express Gen3 x8, Gen4 x8 compatible > DMA IP for complete end-to-end solution
Exceptional DSP Compute in its Class	<ul style="list-style-type: none"> > Highest bandwidth in a cost-optimized FPGA > 1,860 GOP/s, 620 GFLOPs (FP32) in the largest device > Up to 50% fewer resources for equivalent computation vs. Artix-7 FPGAs
Safety and Multi-Level Security Features	<ul style="list-style-type: none"> > RSA-2048 authentication to verify design source > NIST AES-CGM decryption approved, for faster configuration > Permanent tamper penalty to prevent adversaries from accessing security features > Security monitoring IP to adapt to security threats across the product life cycle
DDR4-2400 Performance	<ul style="list-style-type: none"> > DDR4-2400 for highest memory interface performance in a cost-optimized FPGA > Memory bandwidth to match on-chip compute > Reduced memory controller fabric utilization and power vs. Artix-7 FPGAs
Outstanding MIPI and LVDS Performance	<ul style="list-style-type: none"> > Up to 2500Mb/s MIPI and LVDS performance > Support for advanced vision sensors (MIPI, SLVS-EC)
Analog Mixed-Signal Monitoring Block	<ul style="list-style-type: none"> > Voltage, current, and temperature tracking for safe, secure, and reliable operation > Helps meet requirements for key standards: FIPS 140-2, IEC 61508, ISO26262 > Allows for integration of low-amplitude sensors

Scalable to mid- and high-end FPGA families to increase feature-set while preserving design investment

 <ul style="list-style-type: none"> > Up to 308K System Logic Cells > Up to 1,200 DSP Slices > Up to 16Gb/s Transceivers 	 <ul style="list-style-type: none"> > Up to 1,843K System Logic Cells > Up to 3,528 DSP Slices > Up to 32.75Gb/s Transceivers 	 <ul style="list-style-type: none"> > Up to 8,938K System Logic Cells > Up to 12,288 DSP Slices > Up to 58Gb/s Transceivers
---	--	--

TAKE THE NEXT STEP

Artix UltraScale+ FPGAs are supported by comprehensive development tools, reference designs, an IP catalog, and [evaluation platforms](#).

For more information, visit www.xilinx.com/artix-ultrascale-plus.

DISCLAIMERS

(The information contained herein is for informational purposes only and is subject to change without notice. While every precaution has been taken in the preparation of this document, it may contain technical inaccuracies, omissions and typographical errors, and AMD is under no obligation to update or otherwise correct this information. Advanced Micro Devices, Inc. makes no representations or warranties with respect to the accuracy or completeness of the contents of this document, and assumes no liability of any kind, including the implied warranties of noninfringement, merchantability or fitness for purposes, with respect to the operation or use of AMD hardware, software or other products described herein. No license, including implied or arising by estoppel, to any intellectual property rights is granted by this document. Terms and limitations applicable to the purchase or use of AMD's products are as set forth in a signed agreement between the parties or in AMD's Standard Terms and Conditions of Sale.

COPYRIGHT NOTICE

© Copyright 2023 Advanced Micro Devices, Inc. All rights reserved. Xilinx, the Xilinx logo, AMD, the AMD Arrow logo, Alveo, Artix, Kintex, Kria, Spartan, Versal, Vitis, Virtex, Vivado, Zynq, and other designated brands included herein are trademarks of Advanced Micro Devices, Inc. Other product names used in this publication are for identification purposes only and may be trademarks of their respective companies. AMBA, AMBA Designer, ARM, ARM1176JZ-S, CoreSight, Cortex, and PrimeCell are trademarks of ARM in the EU and other countries. PCIe, and PCI Express are trademarks of PCI-SIG and used under license. PID1842500

